

# 75 / 90 / 115

## FourStroke

### Large and in charge

These FourStroke outboards displace 2.1 litres, which means they work smarter – not harder – leading to improved durability and longer life with greater hole shot, superior overall acceleration and top speed.

Less weight matched with higher displacement delivers plenty of torque and immediate power whilst ensuring maximum fuel efficiency, especially when cruising at speeds.

The Focused Mount System limits vibration transmitted to the boat, or to a steering tiller, and a large muffler and sophisticated cowl design reduces engine noise. Combined, these 2.1 litre models are quieter and smoother than any other on the water.

The larger Command Thrust gearcase is available on 90 – 115hp models which has the capability to lift heavier boats onto the plane more easily and hold it there at lower speeds without impacting top speed. A left-hand rotation Command Thrust gearcase is an option on the 115hp to enable dual engine installations.

Combining the perfect balance of performance and economy, this range is ideal for larger fibreglass or aluminium fishing and pleasure boats or heavy-duty commercial applications.



Models	70 EFI	90 EFI	115 EFI / 115 EFI CT
Kilowatts	55.2	66.2	85
Max.RPM at Full Throttle	4500 - 5500	5000 - 6000	5000 - 6000
Cylinders	4 (in-line)	4 (in-line)	4 (in-line)
Smart Craft Compatible	YES	YES	YES
Displacement	2064 cc	2064 cc	2064 cc
Starting	Electric	Electric	Electric
Gear Ratio	2.07:1	2.07:1	2.07:1 / 2.38:1
Gear Shift	F-N-R	F-N-R	F-N-R
Steering Midsection	Remote - BTO	Remote - BTO	Remote - BTO
Alternator System	35 amp (441 W)	35 amp (441 W)	35 amp (441 W)
Fuel System	EFI	EFI	EFI
Trim Positions	EHPT	EHPT	EHPT
Fuel Tank	N/A	N/A	N/A
Fuel Requirements	UL95R	UL95R	UL95R
Weight	163 kg	163 kg	163 kg / 165 kg
Available Boat Transom Heights	L - XL	L - XL	L - XL
Counter Rotation	N/A	N/A	N/A / CXL

**GEAR SHIFT** ..... **DTS:** Digital Throttle and Shift • **F-N-R:** Mechanical Forward Neutral Reverse • **F-N:** Forward Neutral

**STEERING MIDSECTION** ..... **AMS:** Advanced Mid Section • **CMS:** Conventional Mid Section  
**EHPS:** Electric Hydraulic Power Steering  
**BTO:** Big Tiller Optional • **RO:** Remote optional

**ALTERNATOR SYSTEM** ..... **ESM:** On Electric Start Models only • **OPT:** Optional  
**OPT:** Optional 4 amp (50 W) lighting, 2 amp (25 W) charging  
**ML:** ML Models only

**FUEL SYSTEM** ..... **EFI:** Electronic Fuel Injection • **Sci:** Super Charge Injection  
**DFI:** Direct Fuel Injection • **CARB:** through carburetor

**TRIM SYSTEM** ..... **EHTP:** Electric Hydraulic Power Trim and Tilt • **EHT:** Electric Hydraulic Tilt (no Trim) • **GAT:** Gas assist trim • **MTT:** Manual Trim and Tilt  
**SWD:** Shallow Water drive

**FUEL TANK** ..... **INT:** Integrated fuel tank • **RO:** remote optional

**AVAILABLE BOAT TRANSOM HEIGHTS** ..... 381 mm(S) - 508 mm(L) - 635 mm(XL) - 762 mm(XXL)  
**COUNTER ROTATION** ..... 635 mm(CXL) - 762 mm(CXXL)

