



150 FourStroke

Exceeding the boundaries of reliability

Starting with a 3.0 litre block capable of producing more than 250hp, Mariner engineers designed this model to deliver only 150hp and increase the powerhead's long-term durability. Add 10,000 hours of engineering and field testing to the robust gearcase and you've got the most reliable 150hp outboard in the industry.

The 3.0 litre displacement and four-cylinder overhead cam design works less to produce more torque and horsepower so it can go longer and give long-term peace of mind.

With convenient maintenance access to perform basic tasks and a no-spill oil change system, the 150 is super easy to take care of. Plus the small, compact design fits perfectly on a wide range of boats, which also makes it the perfect repower choice.

All this, and it still weighs in at a light, fuel saving 206kg.



Models	150 EFI
Kilowatts	110
Max.RPM at Full Throttle	5000 - 5800
Cylinders	4 (in-line)
Smart Craft Compatible	YES
Displacement	3000 cc
Starting	Electric
Gear Ratio	1.92:1
Gear Shift	F-N-R
Steering Midsection	Remote - CMS - BTO
Alternator System	60 amp (756 W)
Fuel System	EFI
Trim Positions	EHPT
Fuel Tank	N/A
Fuel Requirements	UL95R
Weight	206 kg
Available Boat Transom Heights	L - XL
Counter Rotation	CXL

GEAR SHIFT **DTS:** Digital Throttle and Shift • **F-N-R:** Mechanical Forward Neutral Reverse • **F-N:** Forward Neutral

STEERING MIDSECTION **AMS:** Advanced Mid Section • **CMS:** Conventional Mid Section
EHPS: Electric Hydraulic Power Steering
BTO: Big Tiller Optional • **RO:** Remote optional

ALTERNATOR SYSTEM **ESM:** On Electric Start Models only • **OPT:** Optional
OPT: Optional 4 amp (50 W) lighting, 2 amp (25 W) charging
ML: ML Models only

FUEL SYSTEM **EFI:** Electronic Fuel Injection • **Sci:** Super Charge Injection
DFI: Direct Fuel Injection • **CARB:** through carburetor

TRIM SYSTEM **EHPT:** Electric Hydraulic Power Trim and Tilt • **EHT:** Electric Hydraulic Tilt (no Trim) • **GAT:** Gas assist trim • **GMTT:** Manual Trim and Tilt
SWD: Shallow Water drive

FUEL TANK **INT:** Integrated fuel tank • **RO:** remote optional

AVAILABLE BOAT
TRANSOM HEIGHTS 381 mm(S) - 508 mm(L) - 635 mm(XL) - 762 mm(XXL)
COUNTER ROTATION 635 mm(CXL) - 762 mm(CXXL)

