



# 2.5 / 3.5 / 4 / 5 / 6 FourStroke

## Being light and affordable isn't the whole story

Never before has portable power seemed so good. Packed full of features, these engines perfectly pair performance with versatility.

The entire range is capable of multiple trim and shallow water positions plus 360° steering for full thrust in all directions. All of this comes in a compact, lightweight package with a conveniently positioned large grip carry handle.

Precise control, easy to start and low maintenance; the portable Mariner range is fully equipped so you're always ready to go.



Models	2.5	3.5
Kilowatts	2	2.6
Max.RPM at Full Throttle	4500 - 5500	5000 - 6000
Cylinders	1	1
Smart Craft Compatible	N/A	N/A
Displacement	85 cc	85 cc
Starting	Manual	Manual
Gear Ratio	2.15:1	2.15:1
Gear Shift	F-N	F-N
Steering Midsection	Tiller	Tiller
Alternator System	N/A	N/A
Fuel System	CARB	CARB
Trim Positions	4	4
Fuel Tank	0.95 litre INT	0.95 litre INT
Fuel Requirements	UL95R	UL95R
Weight	17 kg	17 kg
Available Boat Transom Heights	S	S - L
Counter Rotation	N/A	N/A

	4	5 / Sailpower	6
Kilowatts	2.9	3.7	4.4
Max.RPM at Full Throttle	4500 - 5500	4500 - 5500	5000 - 6000
Cylinders	1	1	1
Smart Craft Compatible	N/A	N/A	N/A
Displacement	123 cc	123 cc	123 cc
Starting	Manual	Manual	Manual
Gear Ratio	2.15:1	2.15:1	2.15:1
Gear Shift	F-N-R	F-N-R	F-N-R
Steering Midsection	Tiller-RO	Tiller-RO	Tiller-RO
Alternator System	OPT	4 amp (50 W) ML 4 amp (50 W)	OPT
Fuel System	CARB	CARB	CARB
Trim Positions	6 & SWD	6 & SWD	6 & SWD
Fuel Tank	1.1 L INT - RO	1.1 L INT - RO	1.1 L INT - RO
Fuel Requirements	UL95R	UL95R	UL95R
Weight	25 kg	25 kg	25 kg
Available Boat Transom Heights	S - L	S - L - XL S - L	S - L
Counter Rotation	N/A	N/A	N/A

**GEAR SHIFT** ..... **DTS:** Digital Throttle and Shift • **F-N-R:** Mechanical Forward Neutral Reverse • **F-N:** Forward Neutral

**STEERING MIDSECTION** ..... **AMS:** Advanced Mid Section • **CMS:** Conventional Mid Section  
**EHPS:** Electric Hydraulic Power Steering  
**BTO:** Big Tiller Optional • **RO:** Remote optional

**ALTERNATOR SYSTEM** ..... **ESM:** On Electric Start Models only • **OPT:** Optional  
**OPT:** Optional 4 amp (50 W) lighting, 2 amp (25 W) charging  
**ML:** ML Models only

**FUEL SYSTEM** ..... **EFI:** Electronic Fuel Injection • **Sci:** Super Charge Injection


**DFI:** Direct Fuel Injection • **CARB:** through carburetor  
**TRIM SYSTEM** ..... **EHPT:** Electric Hydraulic Power Trim and Tilt • **EHT:** Electric Hydraulic Tilt (no Trim) • **GAT:** Gas assist trim • **GMTT:** Manual Trim and Tilt  
**SWD:** Shallow Water drive

**FUEL TANK** ..... **INT:** Integrated fuel tank • **RO:** remote optional


**AVAILABLE BOAT**

**TRANSOM HEIGHTS** ..... 381 mm(S) - 508 mm(L) - 635 mm(XL) - 762 mm(XXL)


**COUNTER ROTATION** ..... 635 mm(CXL) - 762 mm(CXXL)




2.5hp & 3.5hp



2.5hp short shaft only



4hp, 5hp & 6hp



4hp, 5hp & 6hp